SEO-SW8



SEO-SW8 - is a pendant mount subwoofer featuring with 8” subwoofer in rounded-edge PP driver unit. High-quality polypropylene enclosure and acoustic engineering craftsmanship guarantees premium performance for demanding applications.
A continuous power handling of 50 Watt (RMS) and maximum power handling of 100 Watt is achieved. Connections are made through a terminal block connector behind the rear cover with a power tap 100V line transformer with tappings for 50W, 25W, 12.5W, 6.25W and a 4Ohm connection.
Mounting the speaker is done through a connection cable with two integrated steel cores for suspending with an additional drop safety. Fixation is made through two snap-hooks on one end and a dual fixation on the other end. Rear cover of the speaker can be placed after installation and hides the connection and suspension on the speaker end.

Feature:



. Indoor public address (PA) system pendant mount subwoofer .
Commercial audio pendant mount subwoofer with transformer .
Pendant mount subwoofer for background music and paging system
. Indoor Applications: Restaurants, Offices, Auditoriums, Gymnasiums and shopping mall
. IP55 for indoor pendant speaker with safety hanging wire
. UV-resistant ABS cabinet & aluminium alloy grille for durable use in black
. 8” subwoofer in rounded-edge PP driver unit
. 100V power taps 50/25/12.5/6.25W & 4Ω

Specification:

SKU	**SEO-SW8**
Type	Pendant Mount Subwoofer
Rated Power	50W at 4Ohm/100V
Input Options	4Ohm / 100V
Transformer Taps	6.25W / 12.5W / 25W / 50W / 4Ohm
Ways	1
Drivers	8”
Effective frequency range	30 - 1000Hz
Sound Pressure Level	101dB
Sensitivity	90dB, measured at 1W/m
Coverage angle	112º Conical
Enclosure material	UV-resistant ABS
Grille	Aluminium alloy
Finished colour	Black (SEO-SW8B)
Waterproof degree	IP55
Dimension (ØxD)	373x253mm
Weight	5.5kg
Included Accessories	Brackets / Safety Rope / Grille

SEO-SW8

FREQUENCY RESPONSE



