SEO-8



SEO-8 - is a 2-way pendant loudspeaker featuring a 8” driver combination with a coaxially mounted 1.5” soft dome tweeter. The 2 way combination with a high-quality polypropylene enclosure and acoustic engineering craftsmanship guarantees premium performance for demanding applications. A continuous power handling of 50 Watt (RMS) and maximum power handling of 100 Watt is achieved. Connections are made through a terminal block connector behind the rear cover with a power tap 100V line transformer with tappings for 50W, 25W, 12.5W, 6.25W and a 8 Ohm connection. Mounting the speaker is done through a connection cable with two integrated steel cores for suspending with an additional drop safety. Fixation is made through two snap-hooks on one end and a dual fixation on the other end. Rear cover of the speaker can be placed after installation and hides the connection and suspension on the speaker end.



Feature:

. Indoor public address (PA) system pendant speaker
. Commercial audio pendant speaker with transformer
. Indoor Applications: Restaurants, Offices, Auditoriums, Gymnasiums and shopping mall
. IP55 for indoor pendant speaker with safety hanging wire
. UV-resistant ABS cabinet & aluminium alloy grille for durable use in black
. 8” low-middle range woofer and 1.5 ” tweeter two way speaker system
. 100V power taps 50/25/12.5/6.25W & 8Ω

Specification:

SKU	**SEO-8**
Type	Pendant Speakers
Rated Power	50W at 8Ohm/100V
Input Options	8Ohm / 100V
Transformer Taps	6.25W / 12.5W / 25W / 50W / 8Ohm
Ways	2
Drivers	8” low-middle range woofer
	1.5 high frequency tweeter
Effective frequency range	30Hz - 20KHz
Sound Pressure Level	109dB
Sensitivity	98dB, measured at 1W/m
Coverage angle	112º Conical
Enclosure material	UV-resistant ABS
Grille	Aluminium alloy
Finished colour	Black (SEO-8B)
Waterproof degree	IP55
Dimension (ØxD)	373x253mm
Weight	5.5kg
Included Accessories	Safety Rope / Grille

FREQUENCY RESPONSE



