SEO-4





SEO-4 - is a 2-way pendant loudspeaker featuring a 4” driver combination with a coaxially mounted 0.75” soft dome tweeter. The 2 way combination with a high-quality polypropylene enclosure and acoustic engineering craftsmanship guarantees premium performance for demanding applications.

A continuous power handling of 20 Watt (RMS) and maximum power handling of 40 Watt is achieved. Connections are made through a terminal block connector behind the rear cover with a power tap 100V line transformer with tappings for 20W, 10W, 5W, 2.5W and a 8 Ohm connection.

Mounting the speaker is done through a connection cable with two integrated steel cores for suspending with an additional drop safety. Fixation is made through two snap-hooks on one end and a dual fixation on the other end. Rear cover of the speaker can be placed after installation and hides the connection and suspension on the speaker end.

Specification:

SKU	**SEO-4**
Type	Pendant Speakers
Rated Power	20W at 8Ohm/100V
Input Options	8Ohm / 100V
Transformer Taps	2.5W / 5W / 10W / 20W / 8Ohm
Ways	2
Drivers	4" low-middle range woofer
	0.75" high frequency tweeter
Effective frequency range	90 - 18KHz
Sound Pressure Level	102dB
Sensitivity	87dB, measured at 1W/m
Coverage angle	92º Conical
Enclosure material	ABS reinforced with fibreglass
Grille	Steel
Finished colour	White (SEO-4W), Black (SEO-4B)
Waterproof degree	IP55
Dimension (ØxD)	137x188mm
Weight	1.55kg

SEO-4

Impedance VS SPL Diagrams





