FLOW-S8AP

The FLOW-S8AP is a 8" two-way, 150-watt active speaker system with a built-in DSP processor and Dante module. It can be used for both main sound and stage monitoring. The system's enclosure features a bass reflex port for enhanced low frequencies and increased sound pressure.



- 1.4" high-frequency driver and 8" woofer
- Built-in Dante module
- Durable powder-coated finish, metal grille
- Cabinet material: 12mm thick professional plywood
- Setting up DSP using software
- Remote control: RS232, RS485, TCP/IP
- Simultaneous control of up to 254 systems
- Compatible with the FLOW-BR1 wall mount

Specification:

SKU	FLOW-S8AP
Type	Professional Active Speakers
Rated Power	150 W (AES)
Nominal Impedance (±20%)	8Ohms
Peak Power	600 W
Ways	2
Low frequency driver	1×8"
High frequency driver	1×1.4"
Frequency Response (-10 dB)	80 Hz-20 kHz
Sensitivity (±2 dB)	93 dB/W/m
Sound Pressure Level	≥114 dB
Total Harmonic Distortion	≤1%
Coverage angle (H*V)	100° x 60°
Power Amplifier Output	≥200 W at 4 ohms (conversion efficiency ≤1%)
DSP Functions	Compressor, Limiter, Noise Gate, Parametric EQ, Matrix Routing, Delay, Filter
Connection type	1x XLR IN 3-pin (female) 2x RJ45 (female), Dante, TCP/IP
Cabinet material	Professional plywood, 12mm
Surface treatment	Black bright spot paint
Mounting bracket	FLOW-BR1 (optional)
Power supply:.	AC 100-240V
Dimension (W×D×H)	250×247×415mm
Net weight:	14kg

FLOW-S8AP

FREQUENCY RESPONSE

